



Carbine Hooks

standard type

- **Material** : mild steel
- **Finish** : electro-galvanised
- **Note** : the minimum breaking load shown below is for guidance only
the product is not suitable for lifting purposes

diameter	length	width	width inside	width inside	minimum breaking load	weight per 100 pcs
a mm	b mm	c mm	d mm	e mm	kg	kg
4	40	14	5	7	-	0.6
5	50	16	7	8	100	0.8
6	60	18	7	9	120	1.6
7	70	22	9	10	180	2.6
8	80	24	11	12	300	4.4
9	90	26	11	12	330	6.4
10	100	30	12	15	460	9.3
11	120	36	14	18	600	12.5
12	140	40	16	20	680	19.5
13	160	44	20	22	800	25.0
14	180	48	20	28	860	35.0
15	200	52	22	29	920	45.0



Carbine Hooks

with pressed thimble

- **Material** : mild steel
- **Finish** : electro-galvanised
- **Note** : the minimum breaking load shown below is for guidance only
the product is not suitable for lifting purposes

diameter	length	diameter inside thimble	width	minimum breaking load	weight per 100 pcs
a mm	b mm	c mm	d mm	kg	kg
4	40	4	14	-	0.8
5	50	5	16	100	1.6
6	60	6	18	120	2.6
7	70	7	22	180	4.4
8	80	10	24	300	6.4
9	90	12	26	330	9.3
10	100	13	30	460	12.5
11	120	13	36	600	19.5
12	140	15	40	680	25.0
13	160	17	44	800	35.0