

MANUFACTURED TO :- BS EN 1492-2000 FLAT WOVEN WEBBING SLINGS,MADE OF MAN MADE FIBRES, FOR GENERAL PURPOSE USE INCLUDES, Scope, Terms & Definitions, Hazards, Safety Requirements, Testing, Marking, Safe Use



TYPE S - SIMPLEX
SINGLE THICKNESS WEBBING SLING



TYPE D - DUPLEX
DOUBLE THICKNESS WEBBING SLING



TYPE D - D - DP
DOUBLE THICKNESS WEBBING SLING
WITH STEEL FITTINGS



TYPE E - ENDLESS
SINGLE THICKNESS ENDLESS WEBBING SLING

This chart indicates the **W.L.L. Working Load Limit**, for webbing slings in a straight lift. Please refer to the chart overleaf for W.L.L. in various modes of lift

	WIDTH mm		WIDTH mm		WIDTH mm	COLOUR	W.L.L. TONNES
S1	60	D1	30	E1	30	VIOLET	1
S2	120	D2	60	E2	60	GREEN	2
S3	180	D3	90	E3	90	YELLOW	3
S4	240	D4	120	E4	120	GREY	4
S5	300	D5	150			RED	5
		D6	180			BROWN	6
		D8	240			BLUE	8
		D10	300			ORANGE	10

SAFETY REQUIRES PERMANENT SUPERVISION

We recommend the following procedure:

1. Lay the sling on a flat surface in a well lit area.
2. Examine sling throughout its length on both sides for surface chafe, cross or longitudinal cuts or any damage to the eyes, stitching, coupling components or fittings.
3. When not in use slings should be stored in clean, dry and well ventilated conditions at ambient temperature and on a rack away from contact with chemicals.



CLEARLY DEFINED LABEL