



# Piling Shackles

## long dee type with type A screw collar pin

- **Material** : body and pin high tensile steel
- **Safety Factor** : MBL equals 5 x WLL
- **Finish** : self colour
- **Certificates** : as standard a works certificate is supplied  
also upon request a certificate of basic raw material  
and/or an EC declaration of conformity

working load limit	diameter bow	diameter pin	diameter eye	width inside	length inside	weight each
tons	a mm	b mm	c mm	d mm	e mm	kg
1.00	13	16	32	22	152	0.55
1.50	16	19	38	32	203	0.95
2.00	19	22	45	38	203	1.64
3.00	22	25	50	45	254	2.29
3.75	25	28	57	50	254	3.40
5.00	28	32	64	54	305	5.05

In inch

working load limit	diameter bow	diameter pin	diameter eye	width inside	length inside	weight each
tons	a inch	b inch	c inch	d inch	e inch	lbs
1.00	1/2	5/8	1 1/4	7/8	6	1.21
1.50	5/8	3/4	1 1/2	1 1/4	8	2.09
2.00	3/4	7/8	1 3/4	1 1/2	8	3.61
3.00	7/8	1	2	1 3/4	10	5.04
3.75	1	1 1/8	2 1/4	2	10	7.48
5.00	1 1/8	1 1/4	2 1/2	2 1/8	12	11.11