



## Green Pin® Open Sockets

### wedge type

- **Material** : high tensile steel GS21Mn5
- **Safety factor** : MBL equals 5 x WLL
- **Finish** : painted green or hot dipped galvanised
- **Certification** : a works certificate and a proof load test certificate can be supplied upon request

number	working load limit	diameter wire rope	length	length to center pin	width inside	diameter pin	thickness side plates	diameter eye	weight each
	tons	mm	a mm	b mm	c mm	d mm	e mm	f mm	kg
0.25	1.25	7 - 8	129	110	18	16	9	36	0.8
0.5	2	9 - 10	165	142	20	20	11	46	1.7
1	3.2	11 - 13	174	146	25	25	12	57	2.1
2	5	14 - 16	211	176	31	30	15	70	4.0
3	6.3	18 - 19	252	212	38	35	16	80	7.0
4	8	20 - 22	288	240	44	41	19	95	10.0
5	12.6	24 - 26	329	274	51	51	22	110	15.0
6	16	27 - 29	375	310	57	57	25	130	21.0
7	20	30 - 32	423	350	63	64	28	146	31.0
8	20	34 - 36	474	400	69	64	28	148	37.0
9	25	37 - 39	527	450	76	70	30	153	51.0
10	32	40 - 42	580	500	76	76	33	160	64.0
11	40	43 - 48	643	550	89	89	39	186	96.0
12	50	49 - 52	737	640	101	95	46	194	130.0
13	64	54 - 58	775	660	114	108	54	230	180.0
14	80	60 - 68	960	835	127	121	60	250	275.0
15	90	72 - 76	1130	1000	146	133	76	270	440.0
16	100	81 - 86	1250	1100	159	140	79	300	510.0

## Gold Nose™ Closed Sockets

### spelter type

- **Material** : drop forged alloy steel SCM 435
- **Finish** : galvanised
- **Certification** : a works certificate and a proof load test certificate can be supplied upon request

diameter wire	length	width	thickness bow	width	length eye	width eye	thickness	weight each
inches	a mm	b mm	c mm	d mm	e mm	f mm	g mm	kg
1 1/4 - 1 3/8	246	122	38	48	83	76	97	18.0
1 1/2 - 1 5/8	305	152	40	57	104	92	123	22.0
1 3/4 - 1 7/8	356	178	47	66	121	112	140	28.0
2 - 2 1/8	391	202	53	76	133	121	158	32.0
2 1/4 - 2 3/8	438	221	61	80	146	133	184	44.0
2 1/2 - 2 5/8	457	264	68	96	165	149	217	56.0
2 3/4 - 2 7/8	540	273	74	105	178	163	222	68.0
3 - 3 1/8	584	295	76	115	194	174	243	100.0
3 1/4 - 3 3/8	626	319	82	121	216	194	260	120.0
3 1/2 - 3 5/8	670	340	92	127	219	202	270	145.0
3 3/4 - 3 7/8	698	356	98	133	235	214	290	190.0
4 - 4 1/4	803	412	112	152	270	242	318	250.0